

SKY PANEL RESP23



LEVHA TEKNİK ÖZELLİKLERİ / SHEET TECHNICAL PROPERTIES

ALAŞIM-KONDİSYON / ALLOY	5005 / H24 - 3105 / H24 - 5754 / H22	
BOYUT TOLERANSLARI / DIMENSION TOLERANCES	EN / WIDTH	Max 1500 mm (-0 mm / +4 mm)
	BOY / HEIGHT	Max 3000 mm (-0 mm / +4 mm)
LEVHA KALINLIĞI / SHEET THICKNESS	2 MM / 3 MM (+/- 0,2 mm)	
ELASTİSİTE MODÜLÜ / ELASTICITY MODULES	-70.000 Mpa	

YÜZEY İŞLEM SEÇENEKLERİ / SURFACE OPTIONS

TOZ BOYA / POWDER COATING	RENK / COLOUR	TÜM RAL RENKLERİ / ALL RAL COLOURS
	ALAŞIM / ALLOY	5005/H24 - 3105/H24 - 5754/H22
	BOYA KALINLIĞI THICKNESS OF PAINTING	60-80 MİKRON / MICRON
	STANDART / STANDART	QUALICOAT-SEASIDE
	YANGIN SINIFI FIRE RESISTANCE CLASS	A2 s1 d0 (EN 13501)
PVDF YAŞ BOYA / LIQUID PAINT	RENK / COLOUR	TÜM RAL RENKLERİ / ALL RAL COLOURS
	ALAŞIM / ALLOY	5005/H24 - 3105/H24 - 5754/H22
	BOYA KALINLIĞI THICKNESS OF PAINTING	25 MİKRON / MICRON
	STANDART / STANDART	ECCA (EN 13523)
	YANGIN SINIFI FIRE RESISTANCE CLASS	A1 (EN 13501)
ELOKSAL / ANODIC OXIDATION	RENK / COLOUR	NATURAL ELOKSAL ve ANALOG RENKLER
	ALAŞIM / ALLOY	5754 / H22
	ELOKSAL KALINLIĞI THICKNESS OF ELOXAL COATING	15-20 MİKRON / MICRON
	STANDART / STANDART	EN 17611 / QUALANOD
	YANGIN SINIFI FIRE RESISTANCE CLASS	A1 (EN 13501)